

FLOAT MODEL EVAPORATOR



Turbo-mist

Standard unit pumps 80 gpm aloft

Turbo-mist

25% evaporation rate would yield 864,000 gallons per month evaporated

Turbo-mist

50% evaporation rate would yield 1.728 million gallons per month evaporated

Turbo-mist

Eliminate all head problems with float model

Turbo-mist

Eliminate drift problems with windy conditions when must contain within a liner

Turbo-mist

Can add a second unit and utilize one pump for both

Turbo-mist

Monthly maintenance allows 24/7 operation rain or shine

Turbo-mist

Corrosive waste not a problem for floats or machine.

Turbo-mist

Pump system can be deducted if pumping with 150 psi on 2-inch line available

Turbo-mist

Standard system includes self-cleaning filter system

1-800-495-6145

<http://www.turbomistevaporators.com>

Turbo-mist

SLIMLINE MANUFACTURING LTD.

TRAILER MODEL EVAPORATOR



Turbo-mist

Self contained unit with pump and self-filtering system

Turbo-mist

Can be towed around job site

Turbo-mist

Has built in control panel with low pressure shut down

Turbo-mist

One person to adjust to wind conditions can turn wind tunnel

Turbo-mist

Standard unit pumps 80 gpm aloft

Turbo-mist

25% evaporation rate would yield 864,000 gallons per month evaporated

Turbo-mist

50% evaporation rate would yield 1.728 million gallons per month evaporated

Turbo-mist

Can add a second unit and utilize one pump for both

Turbo-mist

Monthly maintenance allows 24/7 operation rain or shine

Turbo-mist

Units are powder coated to allow use in highly corrosive waste situations

1-800-495-6145

<http://www.turbomistevaporators.com>